

ALS-Product Specification

ALS-HH500 H.264 HDTV IP Fix Dome

Product Key Features:

- Standard H.264 – the Blu-Ray DVD video quality
- HDTV Dual Video Streaming
- Megapixels CMOS Sensor Progressive Scan
- Day / Night
- 802.3af PoE embedded
- Hybrid IP & Analog HDTV
- Vandalproof Enclosure

HDTV



ALS-HH500 is the cost effective high definition camera hybrid H.264 IP HDTV and YPbPr HDTV. it uses standard H.264 to compress megapixels progressive scan CMOS video image at the Blu-Ray DVD quality in full motion HD 720p at 2Mbps only! beside, the live video and recorded video are compliant to standard H.264 AVC codec, VLC / quick time / core player can play them directly.

In addition, the YPbPr analog HDTV output brings the most cost effective HD video for the current HD video conference market.

ALS-HH500 Applications:

- HD City Surveillance
- HD Environmental Surveillance
- HD Traffic Monitoring
- HD Video Conference

ALS-HH500 Technical Specification

Digital Video Processor:

Compression Technology	: Standard H.264
Frame Rate	: 30fps at 720p
Video Protocol	: TCP/IP, UDP, PPPoE, RMTP, ARP, DDNS, FTP, RTSP
CPU	: 240 MHz ARM926
Camera Access	: 25 users (need MPXP relay server)
Bit Rate	: 10Kbps ~ 2Mbps
Video Size	: 1280*720 / 720*576 / 352*288
Ethernet	: 10/100

Camera System:

CMOS Sensor	: 1/4" megapixels
SYNC System	: Internal
Minimum Illumination	: 0.8 Lux F1.2 5600K
Resolution	: megapixels
S/N Ratio	: 52db (MIN) / 60 db (TYP) (AGC OFF)
White Balance	: ATW / AWB (3200 ~ 10000K)
Auto IRIS	: A.E.S / DC-IRIS
Electronic Shutter	: 1/50~1/120,000 sec.

Environmental:

LAN Ports	: 10/100 BASE-T, RJ45, 1ea
LED Display	: LAN, Power, Link
Mini SD Card Slot	: SDIO WiFi 54Mbps (option)
Operation Temperature	: -20° ~ 60°
Operation Humidity	: within 85% RH
Power Supply	: 802.3af PoE
Connectors	: RJ45 for IP Connection
Mounting	: Vandalproof Indoor